

ACCEL 7450S

Best in Class Powerful Multi-Form Printing

Handles up to 7-Part Forms

Ideal for F & I Applications

A leader in printing for Automotive Retailing

Handles cut sheet forms up to 37" in length or tractor fed forms

Wide carriage up to 136 columns

Extra long ribbon life

24 Pin Printhead

Print speeds to 528 cps

Replace virtually any 9-pin or 24-pin printer with a standard emulation, or if needed we will prepare an emulation to work with your existing data stream.



7450S Specifications



Print Head: 24 pins and 0.010 inches (diameter of wire)

Resolution: 360 x 360 dpi (Max.)

Character Set: ASCII: 17 international character sets

Code Page: U.S.A, MULTI, PORTUGAL, CANADA, NORWAY, EAST EURO, CYRILLIC, RUSSIAN, HUNGARY, KAMENICKY, TURKEY, ICELAND, BULGARIA, MAZOVIA, GRK 437, GRK 851, GRK8859-7, GRK 1253, ARAB NLS, ARAB EXT, WIN LAT1, WIN LAT2, ISL LTN1, ISO LTN2, TUR8859-9, ISO LTN9, KBL, LATIN 7

Fonts: ASCII: Draft, Roman, Sans Serif, Courier, Prestige, Script, OCR-B, OCR-A, Orator

Note: In high speed mode or super high mode, printer would automatically change the ASCII font to Draft when printing ASCII characters.

Bar Codes: EAN-13, EAN-8, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code 128 B, Code 128 C, NW-7

Character Pitch: ASCII: 10 CPI, 12 CPI, 15 CPI, 17 CPI, 20 CPI, proportional

Line Space: 1/3 inch, 1/4 inch, 1/6 inch, 1/8 inch, 1/9 inch and n/360 inch

Paper Feeding Speed (Max): 6 inches per second (continuous feed)

Printing Direction: Bi-directional logic seeking

Ribbon Life: 20 million characters (draft mode)

Emulations: EPSON ESC/PK2, OKI5530SC, IBM 23912391

Interfaces: USB interface: 2.0 Full-Speed, RS-232C Serial interface (DB 9-PIN), Optional Ethernet interface

Input Buffer: 132 KB

Control Panel: 8 Buttons + 4 LED indicators + LCD

Printing width: 136 columns (10 CPI) / 13.6 inches

Paper Feed Type: Cut sheet: Load/eject from front; Load from front and eject from rear
Tractor paper: Load from rear, eject from front

Continuous Paper: Width: 5 in ~ 15.98 in

Cut sheet / Card: Width: 5 in ~ 16.93 in / Length: 5 in ~ 16.93 in

Thickness Adjust: Automatically detect the paper thickness and adjust the gap, or adjust through gap adjust lever.

Copies: Up to 7-part forms

Paper Handling: Paper thickness detect, Skew detect, Paper edge detect

Physical Dimensions:
25 in (width) × 13.19 in (depth) × 11.57 in (height) (no tractor and paper rack)
25 in (width) × 18.31 in (depth) × 11.57 in (height) (with tractor and paper rack)

Weight: ~48.5 lbs

Special Functions: LCD, Pin Break compensation, Pin Switch, Automatic Emulation Match

Noise: < 58 dB (A) (ISO7779 standard)

Speed (ASCII)		
Speed	10 CPI	12 CPI
High Density	180 CPS	216 CPS
Normal Speed	240 CPS	288 CPS
High 1	360 CPS	432 CPS
High 2	440 CPS	528 CPS

Corporate Headquarters
803 Camarillo Springs Road, Suite D,
Camarillo, CA 93012
(805) 388-5799 PH
(805) 484-5282 FX

www.amtdatasouth.com

Charlotte Operation
5033 Sirona Drive, Suite 800
Charlotte, NC 28273
(704) 523-8500 PH
(704) 525-6104 FX