

Fastmark® PT-2



Fastmark PT-2

Ideal for Barcoded Labels and Wristbands or for Receipts

This small and extremely mobile thermal printer comes equipped with our proprietary PAL® programming language plus popular emulations, empowering the printer to fit seamlessly into countless existing networks.

The PT-2 is designed specifically for barcode labeling (linear and 2D), item/asset and shelf tags, receipts and more... making applications for retail, food preparation, healthcare, logistics, warehouse, shipping, process control, industrial/manufacturing, and government easy.

Small, But Powerful

Weighing in at less than one pound, the PT-2 prints at 4 inches per second, has 128 MB Flash memory, 64 MB SDRAM, and it can print more than 17 hours on a single battery charge (using receipts as an example).

PAL®

The AMT Datasouth Difference

For applications with a non-standard emulation or data stream, our proprietary PAL® programming language resides in the (smart) Fastmark PT-2 allowing us to load an app that will accept your data stream and convert (including creating barcodes from the data), format and print to fit your needs. You can unplug whatever your printer is and replace it with the Fastmark PT-2 printer. And, ongoing service and support, including future changes to the PAL app, if needed, are available for the life of the printer.

Fastmark PT-2

The ideal mobile barcode and wristband printer



KEY FEATURES:

IP54-rated environmental case to resist dust and water
Wi-Fi Certified™
Large paper capacity to reduce the frequency of changing paper roll
Lasts more than 17 hours of printing receipts on a single battery charge
ENERGY STAR® qualified
Belt clip

FASTMARK PT-2 SPECIFICATIONS:

Printing Method	Direct Thermal Printing
Resolution	203 dpi
Speed	Up to 4 ips
Command Set	PAL and supports EPL2 and ZPL emulations, ESC-POS, and CPCL emulations
Battery	High capacity 1620 mAh rechargeable Lithium Ion batteries
Dimensions	3.52" (W) x 5.3" (H) x 2.22" (D)
Weight	0.77 lbs
Max Print Width	1.89"
Max Print Length	90"
Drop Specification	5 ft (with IP54 case can be 6.5 ft)
Max Roll Capacity	2" (50 mm) OD
Processor	32-bit RISC CPU

Memory	128 MB Flash memory 64 MB SDRAM
Interfaces	USB 2.0 and either WiFi 802.11 a/b/g/n or Bluetooth 4.0
Sensor	Reflective
Barcodes	Linear and 2D
Media Width	Max 2.28" (58 mm) With adapter: 2" (50.8 mm) and 1" (25.4 mm) (user option)
Warranty	Printer: 2-years

FACTORY OPTIONS:

Bluetooth 4.2 + MFi (for Apple® devices)
NFC
Linerless

USER OPTIONS:

Mini type USB 2.0
USB to RS-232 converter cable
Li-ion battery
Charge station 1 cell (with changeable power connector)
Charge station 4 cell (with changeable power connector)
Vehicle power adapter
IP54-rated environmental case with shoulder strap
12-24V DC automobile cigarette lighter plug
Adapters for 1" or 2" media roll width
Fork truck or cart mount

Contact

Get in touch with us today to see if one of our solutions can help you with your printing needs and ultimately, your operational challenges.

800-215-9192

kstovall@amtdatasouth.com

AMT Datasouth

www.amtdatasouth.com

Specifications are subject to change without notice.
#20555



Corporate Headquarters
803 Camarillo Springs Road, Suite D,
Camarillo, California 93012
(805) 388-5799 PH • (805) 484-5282 FX

Charlotte Operation
5033 Sirona Drive, Suite 800
Charlotte, NC 28273
(704) 523-8500 PH • (704) 525-6104 FX

