

Fastmark[®] M35

Portable and Feature-Rich



Compatible with popular emulations or our proprietary PAL[®] smart app with programming language to format to your exact requirements

The Fastmark M35 has a color LCD display and is lightweight (weighing in at under 2 pounds) and mobile. Great for manufacturing, transportation, retail, and healthcare applications. Withstands drops of nearly 6 feet (or over 8 feet with a protective case). Receipts and barcode labels can be printed using direct thermal technology in 203 dpi using up to 3 inch wide media. Couple the Bluetooth version with a Bluetooth scanner for a hassle-free combination. Also equipped with WiFi connection capability.

Equipped with popular emulations or our optional proprietary PAL[®] smart app with programming language that reads the incoming data and formats the output to your requirements.

AMT*datasouth*



Fastmark M35

Small Printer, Big Features



PRINTER SPECIFICATIONS INCLUDE:

Resolution	203 dpi	Bar Code	
Printing Method	Direct Thermal	1D bar code	Code128UCC, Code128 subsets A, B, C, EAN128, Interleaved 2 of 5, with check digit, Standard 2 of 5, Industrial 2 of 5, Code39, Code39 with check digit, Code93, EAN13, EAN8, UPCA, UPCE, EAN and UPC 2 (5) digits add-on, Codabar, Postnet, MSI with check digit, PLESSEY, China post, ITF14, EAN14, Code11, TELEPEN, TELEPEN number, PLANET, Code49, Deutsche Post Identcode and Leitcode, LOGMARS
Print Specifications	Up to 5 ips (max), 2.83" Width, 110" length	2D bar code	CODABLOCK F mode, GS1 DataBar, GS1 DataMatrix, Maxicode, AZTEC, PDF417, QR Code, Micro PDF417, TLC39
Enclosure	Plastic with rubber over molded	Printer Language	PAL®, Compatible to TSPL-EZC (EPL2, ZPL2, CPCL), or ESC-POS
Physical	4.61" (W) x 6.81" (H) x 3.11" (D), 1.64 lbs	Media Type	Die cut, black mark, receipt, fan-fold, linerless, continuous (outside wound)
Drop Specification	6 feet with protective case can be 8.2 feet	Media Width	1" - 3.15"
IP Rating	IP54 (without case, paper path is excluded)	Media Thickness	2.36 ~ 6.3 mil
Label Roll Capacity	2.64 inches (outside diameter)	Media Height	0.5" - 110" 1" - 6" for peeler mode
Processor	32-bit RISC CPU	Media Core Diameter	Standard: 0.5" Optional: 0.75", 1" + 1.5"
Memory	128 MB SDRAM, 128 MB Flash, microSD card reader for Flash memory expansion up to 32 GB	Environmental	Comply with RoHS, REACH, WEEE, REACH
Interfaces	Choose Either: Type C USB 2.0 + MFi Bluetooth 5.0 Type C USB 2.0 + 802.11 a/b/g/n/ac with Bluetooth 5.0 *Type C is for communication only	Limited Warranty	Printer: 2 years Print Head: 1 million inches or 12 months whichever comes first Battery: 1 year
Power	7.4V DC, 3,030mAh Li-ion rechargeable smart battery	Factory Options	Media sensor position (default center, right, or left side)
User Interface	2 LED indicators (battery charging status, printer status), 2.3" color LCD display, 320 x 240 pixels	User Options	Various media cores, protective case, and battery adaptors.
Sensors	Transmissive sensor, Reflective sensor		
Internal Fonts	8 alpha-numeric bitmap fonts Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font		

*All information subject to change without notice and is protected by AMT Datasouth copyright.

AMTDatasouth

Corporate Headquarters

3222 Corte Malpaso
Suite 208
Camarillo, CA 93012
800-215-9192 PH



Charlotte Operations
5033 Sirona Dr., Suite 800
Charlotte, NC 28273
800-476-2120 PH

www.amtdatasouth.com

Printers backed by AMT Datasouth's quality guarantee.