

# Documax 6390

## Multi-Form Printing for any Environment

Handles up to 7-Part Forms

Low Life Costs

24 Pin Printhead, up to 504 cps  
print speed

Replace virtually any 9-pin or  
24-pin printer with a standard  
emulation, or if needed we will  
prepare an emulation to work  
with your existing data stream



For any kind of form that can't be done "electronically" or where a signature or two are needed:

- Finance & Insurance Forms
- Cargo Forms
- Bills of Lading
- Shipping Manifests/Packing Slips
- Basic Invoicing

# 6390 Specifications



**Print Head:** 24 pins and .008 inch (diameter of wire)

**Resolution:** 360 x 360 dpi (Max.)

Character Set: ASCII: 17 international character sets

**Code Page:** U.S.A., MULTI, PORTUGAL, C-FRANCE, NORWAY, E.EUROPE, TURKY853, CYRILLIC, TURKY857, ARABS, RUSSIA, GREEK869, USSRGOST, ISO8859, GRK 437, GRK 851, GRK8859-7, GRK 1253, ARAB NLS, ARAB EXT, WIN LAT1, WIN LAT2, ISO LTN1, ISO LTN2, TUR8859-9, ISO LTN9, KBL, LATIN 7, PC 1256

**Fonts:** Draft, 8 kinds of the LQ fonts: (Roman, Sans Serif, Courier, Prestige, Script, OCR-A, OCR-B, Orator)

**Bar Codes:** EAN-13, EAN-8, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code 128 B, Code 128 C, Codabar

**Character Pitch:** ASCII: 10 CPI, 12 CPI, 15 CPI, proportional

**Line Space:** 1/6 inch, 1/8 inch, or programmable in 1/360 inch increments

**Paper Feeding Speed (Max):** 5.0 inch/s (feeding continuously) / 44ms feeding one line (1/6 inch)

**Printing Direction:** Bi-directional logic seeking

**Emulations:** EPSON ESC/PK2, OKI 5530SC, IBM 2391

**Interfaces:** USB interface: 2.0 Full-Speed, Parallel interface: Centronics (IEEE1284 NIBBLE), Ethernet interface (10/100Base-T)

**Input Buffer:** 256 KB

**Control Panel:** 4 buttons and 4 LED lights

**Printing width:** 82 column (10cpi/8.2 inches)

**Paper Feed Type:** Cut sheet - Load and eject from front, load from front and eject from rear; Continuous paper - Load from rear and eject from front

**Continuous Paper:** Width: 2.4 ~ 11 inches

**Cut sheet:** Width: 2.1 ~ 11.7 inches / Length: 2.6 ~ 21 inches

**Max. Paper Thickness:** 0.078 inch

**Copies:** 7-part forms

**Paper Handling:** Paper edge detection, skew detection, black mark detection, paper thickness auto-adaption, full slot paper feeding

**Physical Dimensions:** 16.6 inches (Width) x 9.4 inches (Length) x 7.9 inches (Height)  
Weight: 11 lbs.

**Power Supply:** Input voltage: 120 V (AC); Frequency: 60Hz

**Noise:** <55 dB (A) (ISO7779 standard)

**Ribbon Life:** 10 million characters (draft mode)

Speed (ASCII)		
Speed	10 CPI	12 CPI
Normal Speed	150 CPS	180 CPS
High Speed	300 CPS	360 CPS
Super High Speed	420 CPS	504 CPS

**Corporate Headquarters**  
803 Camarillo Springs Road, Suite D,  
Camarillo, CA 93012  
(805) 388-5799 PH  
(805) 484-5282 FX

[www.amtdatasouth.com](http://www.amtdatasouth.com)

**Charlotte Operation**  
5033 Sirona Drive, Suite 800  
Charlotte, NC 28273  
(704) 523-8500 PH  
(704) 525-6104 FX